



## J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

<b>TERMINAL PART NUMBER</b>	SPC-1.0
<b>STRIP LENGTH (MM)</b>	6.5

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
0.50 mm <sup>2</sup>	1.10	1.60	*	*	N/A
0.75 mm <sup>2</sup>	1.30	1.60	*	*	N/A
1.00 mm <sup>2</sup>	1.40	1.60	*	*	N/A

### COMMENTS:

\* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

### GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05  
CONDUCTOR WIDTH - +/- 0.05  
INSULATION HEIGHT - N/A  
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
AJS	MS
29-01-01	29-01-01